

ChemScan® UV-2150/S Series
TECHNICAL SPECIFICATION (rev)

FUNCTIONS AND OUTPUTS

Measurement Principle	High Resolution, Ultraviolet Absorbance
Number of Wavelengths	256
Spectral Range	200 - 450 nm
Calibration Technique	Pattern Recognition of Spectral Data
Number of Parameters	Four (special for chloramination monitoring)
Parameter Options	Free, Total Ammonia, Monochloramine, Total Chlorine, UV Absorbance or Transmittance
Data Communications	4 - 20mA (4 outputs max.), RS-232, other formats optional
Data Log	1000 Values Time/Date Stamped, 24 Calibration Spectra
Auto Zeroing	YES (Std)
Auto Cleaning	YES (Std)
Analyzer Pump	YES (Std), Zeroing, Cleaning and Internal Sample Flow Only
Sample Conditioning	YES (Opt), Direct Injection
Number of Sample Lines	1 or 2 through Internal Manifold

PERFORMANCE SPECIFICATIONS²

Reading Interval	10 to 9999 minutes
Response Time	10 minutes for the entire four parameter suite
Range	Free Ammonia 0.02 - 5.00 mg/l as N Total Ammonia 0.02 - 5.00 mg/l as N Monochloramine 0.01 - 10.0 mg/l as Cl ₂ Total Chlorine 0.01 - 10.0 mg/l as Cl ₂ Transmittance 0 – 100% T, Absorbance 0 – 3.000 AU
Accuracy	2% to 5% of Range
Precision	Less than 0.5% of Range
Zero Drift	Less than 0.5% of Range (with Auto Zero)

SAMPLE PARAMETERS

Sample Pressure	Pressurized Sample Lines must be regulated to 10-60 psi
Sample Flow	0.5 to 5.0 l/min. (1.5 l flush/sampling)
Filtration Requirement	NONE (For samples meeting turbidity and solids requirements), Optional ultrafilter available for high solids or turbidity.
Strainer Requirement	Mesh Opening of 2.0 mm Max.
Sample Temperature	1 ^o - 60 ^o C (Std)
Sample Turbidity	0 - 60 NTU (Std)
Sample Suspended Solids	0 - 150 mg/l TSS

MAINTENANCE

Light Source Replacement	Every 5 years
Internal Battery Replacement	Every 2 years
Zero/Clean Solution Refill	As Required (2-4 weeks typ.)
Reagent Refill	As Required (2-4 weeks typ.)

INSTRUMENT SPECIFICATIONS

Size	40 x 20 x 10 in.
Weight	130 lbs.
Mounting	Wall (Std) or Stand (Opt)
Finish Coating	Baked Enamel on Steel (Std) or Stainless Steel (Opt)
Power	120 VAC ±10%, 50-60 Hz, 10 Amps max.
Power Connection	Hard Wired (Std) or Plug (Opt)

Power Condition Dedicated Branch Circuit Free From: Surges/Dips > 10%, RF and

Operator Interface	Switching Noise
Sample Cell Material	2 x 20 LCD and 4 x 4 Keypad
Sample Connection	Polymer Body with Quartz Windows
Waste Connection	1/4" FNPT Fitting
	1/4" FNPT Fitting (Open Drain Required)

OPERATING ENVIRONMENT

Enclosure Ratings	NEMA 4 (Main Enclosure)
	NEMA 3R (Optrode Enclosure)
Ambient Temperature	5 ^o - 35 ^o C (Std)
Relative Humidity	0 - 100% (Non-Condensing)

Notes:

1. Technical Specifications are subject to change without prior notice.
2. All performance specifications are based on analysis of drinking water standards under factory conditions.